




Arendal 1560XX0012 23.07.2021 v.12.7 www.norlys.com





Type of luminaire		
Type of lumianire	Bollard.	
Photometric body	Uncovered light.	
Characteristics of the luminaire Modern design luminaire with a combination of decorative crystal lar and durable and stable casing		

General information	
Materials	Hot-dip galvanized and powder-coated steel. Lens - crystal glass, satin inside. Lens may change to light amber colour over time.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø65mm every 120°.
Terminal	Connection terminals: max 3x4mm², possibility to connect luminaire in loop max 3x2,5mm². Round insulated cable with a diameter of max ø12,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	14,26kg / 15,71kg
Box dimensions [cm]	97x18,5x18,5

Technical data	
E27 lamp	QA55 / LED A5560
Light source wattage	max 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class A+ D

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold separately	
205ZX0010	Concreting anchor
206GA0010	Ground anchor
206GA0S10	Anchoring support
46999021	LED E27 lamp

Recommended light sources				
Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27			
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27			

Spare	parts	

915600229 Lens.

## Files to download

Manual

Indexes		
Index	Color	RAL
1560B	BLACK	9005
1560GA	GALVANIZED	-
1560GR	GRAPHITE	7016



