




NICO

aluminium, szkło / aluminium, glass /
алюминий, стекло

9517 ● GR

2×GU10, max 10W
IP 54

NICO

aluminium, szkło / aluminium, glass /
алюминий, стекло

9518 ● GR

1×GU10, max 10W
IP 54

ARRIS

aluminium, szkło / aluminium, glass /
алюминий, стекло

9515 ○ SI

2×GU10, max 10W
IP 54

ARRIS

aluminium, szkło / aluminium, glass /
алюминий, стекло

9516 ○ SI

1×GU10, max 10W
IP 54

HANOI LED

aluminium / aluminium / алюминиевый

9512 ○ WH

HAVANA LED

aluminium / aluminium / алюминиевый

9511 ○ WH

LIMA LED

aluminium / aluminium / алюминиевый

9510 ○ WH

Item No.	POWER	COLOUR TEMP.	LUMINOUS FLUX	BEAM ANGLE	COLOUR RENDERING INDEX (CRI ≥)	SAFETY TYPE	INPUT	POWER FACTOR	INGRESS PROTECTION	LIFETIME
9512	6W LED	3000K	335 lm	92°	80	⊕	~220-240V, 50Hz	0,55	IP 54	10 000 h
9511	9W LED	3000K	430 lm	106°	80	⊕	~220-240V, 50Hz	0,55	IP 54	10 000 h
9510	6W LED	3000K	360 lm	97°	80	⊕	~220-240V, 50Hz	0,55	IP 54	10 000 h