




ZEM LED
aluminium, szkło / aluminium, glass / алюминий, стекло
4444 ● GR




SEMI LED
aluminium, szkło / aluminium, glass / алюминий, стекло
6775 ● GR




MUNO LED
aluminium / aluminium / алюминий
6776 ● GR



PEAK LED
aluminium, szkło / aluminium, glass / алюминий, стекло
4441 ● GR



DRAS LED
aluminium, szkło / aluminium, glass / алюминий, стекло
4442 ● GR



KHUMBU
aluminium, szkło / aluminium, glass / алюминий, стекло
4443 ● GR
1×G9 max 40W
IP 44

Item No.	POWER	COLOUR TEMP	LUMINOUS FLUX	BEAM ANGLE	COLOUR RENDERING INDEX (CRI >)	INPUT	SAFETY TYPE	POWER FACTOR	INGRESS PROTECTION	INGRESS PROTECTION
4444	4x1W LED CREE	3000K	321 lm	16°	80	~200-240V, 50Hz	⊕	0,89	IP 54	10 000 h
6775	36x0,2W LED CREE	3000K	242 lm	120°	80	~220-240V, 50Hz	⊕	0,54	IP 54	8 000 h
6776	1x6W LED CREE	3000K	242 lm	120°	80	~220-240V, 50Hz	⊕	0,54	IP 54	8 000 h

Item No.	POWER	COLOUR TEMP	LUMINOUS FLUX	BEAM ANGLE	COLOUR RENDERING INDEX (CRI >)	INPUT	SAFETY TYPE	POWER FACTOR	INGRESS PROTECTION	LIFETIME
4441	2x3W LED CREE	3000K	62 lm	83°	80	~200-240V, 50Hz	⊕	0,91	IP 54	10 000 h
4442	2x3W LED CREE	3000K	122 lm	65°	80	~200-240V, 50Hz	⊕	0,91	IP 54	10 000 h