



Product Datasheet

06 Downlights Fixed LED>The 40W Backlit Panel

50140B/W/D



60x60 recessed backlit LED panel for T-rail false ceilings. Uniform lighting, ideal for commercial applications.

Complete with 850mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Related items



050017



050108

Physical Specification

Item Group
Family

06 Downlights Fixed LED
The 40W Backlit Panel



Order Code	50140B/W/D	Завантажено з e27.com.ua
Colour	White	
Material	Aluminium + Steel	
Shape	Rectangular	
Length	595mm	
Width	595mm	
Height	29mm	
Recessed T-Ceiling	Yes	
Depth Required	50mm	
Indoor	Yes	
Adjustable	No	

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting		
Input Type	Constant Current	
Input Current	850mA	
Voltage	45V	
Safety Class		

Power(Watts)	38,7W	Завантажено з e27.com.ua
IP Rating	IP20	
Light Source	LED built in	
LED Type	SMD 2835	
LED Brand	Samsung	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	32,3-38,25W
Power Factor	0,9
Constant Current	Yes
850mA	38-45V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Cable Length	50cm
Brand	ONE

Illumination Data

Colour Temperature	6000K
Lumen Output	4000lm
Light Efficiency	100lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

Box Weight	2.300kg
Pcs/Carton	4
Barcode	5291889071105
HS Code	9405119090

Certification & Warranty

Warranty	3 years
Weee Directive	Yes

switch to
one light!

